

# PRODUCT DATA SHEET

## VERDEEN ENHANCEMENT

### *Lube Booster Catalyst - EXTREME*

VERDEEN ENHANCEMENT is a booster catalyst for lubricants specially formulated to improve the high-performance and quality of lubricants. A robust and balanced combination of "Green Nano-Technology" has resulted in a lubricant with high stability and homogeneity and significantly increased the lubricant's ability to provide superior engine protection, reduces friction coefficient, stabilizes engine temperature, and increases engine power.

### Features and Benefits

- ❖ *Maintains Stability of Viscosity and Increases Engine Lubrication*; Extended viscosity grade coverage and increased stability for all seasons and extreme climate applications.
- ❖ *Reduces Friction and Lowering Engine Temperature*; advanced protection technology will reduce engine friction, reduce engine noise, and stabilize engine temperature
- ❖ *Extends Mileage of Engine Oil*; Lubricants have better heat resistance, are more homogeneous and stable. Lowering friction and better lubrication will maintain the engine from overheating so that the lubricants will not disintegrate easily
- ❖ *Reduces Wear of The Metal*; Lubricants have possessed antioxidant that will help prevent rust formation, the engine stays clean and reduces wearing out
- ❖ *Reduces Emission Levels*; Superior lubricant that makes the engine not overheating thereby preventing NOx and reducing exhaust emissions

### Technical Data Properties

Parameters	Unit	Method	Typical Results
Appearance	-	Visual	Clear / Light Gold
Viscosity, Kinematic @40°C	cSt	ASTM D 445	8.00 – 9.25
Density @15°C	Kg/L	ASTM D 2270	0.89 – 0.96
Flash Point	°C	ASTM D 92	Min 90.0
Pour Point	°C	ASTM D 97	Max -20.0
Ash Content	%wt	ASTM D 874	Max 0.01
Total Acid Number	mg KOH/g	ASTM D 664	4.0 – 5.0

Product Number: VE1005

Available Pack: 20 L and 200 L

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY

### Recommended Dosage

- Pour 2 - 4 mL Verdeen Enhancement | Lube Enhancer Catalyst to 1 L of Lubricants
- Stir Lubricants that contain Verdeen Enhancement | Lube Enhancer Catalyst for 4 hours
- Settling Lubricants at least 1 x 24 hours before use

### Handling Information

- In case of eye contact, wash with water for at least 15 minutes
- Do not ingest. If ingested drink a large volume of water
- Do not induce vomiting
- Call physician immediately



### PT ISLAVERDE BIOINNOVATION UTAMA

📍 Jl. Gunung Sahari Raya No. 32, Jakarta Pusat 10720

☎ +62 21 625 7555

✉ [info@verdeen.id](mailto:info@verdeen.id)

🌐 [www.verdeen.id](http://www.verdeen.id)

